

globus authz Reference Manual

2.1

Generated by Doxygen 1.3.9.1

Thu Jan 26 15:23:13 2012

Contents

1 globus authz Module Index	1
2 globus authz Module Documentation	1

1 globus authz Module Index

1.1 globus authz Modules

Here is a list of all modules:

GSI Authorization API	1
GSI Credential Constants	3

2 globus authz Module Documentation

2.1 GSI Authorization API

Initialize Handle

- `globus_result_t globus_gsi_authz_handle_init (globus_gsi_authz_handle_t *handle, const char *service_name, const gss_ctx_id_t context, globus_gsi_authz_cb_t callback, void *callback_arg)`

Authorization decision made here

- `globus_result_t globus_gsi_authorize (globus_gsi_authz_handle_t handle, const void *action, const void *object, globus_gsi_authz_cb_t callback, void *callback_arg)`

Destroy Handle

- `globus_result_t globus_gsi_authz_handle_destroy (globus_gsi_authz_handle_t handle, globus_gsi_authz_cb_t callback, void *callback_arg)`

Query for authorization identity

- `globus_result_t globus_gsi_authz_get_authorization_identity (globus_gsi_authz_handle_t handle, char **identity_ptr, globus_gsi_authz_cb_t callback, void *callback_arg)`

2.1.1 Function Documentation

2.1.1.1 `globus_result_t globus_gsi_authz_handle_init (globus_gsi_authz_handle_t * handle, const char * service_name, const gss_ctx_id_t context, globus_gsi_authz_cb_t callback, void * callback_arg)`

Initializes a handle.

Parameters:

`handle` Pointer to the handle that is to be initialized

`service_name` Service to authorize access to

context Security context used to contact the service

callback Callback function to call when authz handle init completes

callback_arg Argument to callback function

Returns:

GLOBUS_SUCCESS if successful A Globus error object on failure:

2.1.1.2 globus_result_t globus_gsi_authorize (globus_gsi_authz_handle_t handle, const void * action, const void * object, globus_gsi_authz_cb_t callback, void * callback_arg)

Authorization decision made here.

Parameters:

handle Pointer to the handle that is to be initialized

action Action to authorize

object Object that the action pertains to.

callback Callback function to call when authorization completes

callback_arg Argument to callback function

Returns:

GLOBUS_SUCCESS if successful A Globus error object on failure:

2.1.1.3 globus_result_t globus_gsi_authz_handle_destroy (globus_gsi_authz_handle_t handle, globus_gsi_authz_cb_t callback, void * callback_arg)

Destroy a Globus GSI authz handle.

Parameters:

handle The handle that is to be destroyed

callback Callback function to call when handle is destroyed

callback_arg Argument to callback function

Returns:

GLOBUS_SUCCESS

2.1.1.4 globus_result_t globus_gsi_authz_get_authorization_identity (globus_gsi_authz_handle_t handle, char ** identity_ptr, globus_gsi_authz_cb_t callback, void * callback_arg)

Query for authorization identity.

Parameters:

handle The handle that is to be used for the identity check.

identity_ptr The authorization identity determined by the authorization handle. This is must be freed by the caller. If the value is NULL (and this function returned GLOBUS_SUCCESS), the caller should use the authenticated identity.

callback Callback function to call when identity is determined.

callback_arg Argument to callback function.

Returns:

GLOBUS_SUCCESS

2.2 GSI Credential Constants

Enumerations

- enum `globus_gsi_authz_error_t` {
 GLOBUS_GSI_AUTHZ_ERROR_SUCCESS = 0,
 GLOBUS_GSI_AUTHZ_ERROR_ERRNO = 1,
 GLOBUS_GSI_AUTHZ_ERROR_BAD_PARAMETER = 2,
 GLOBUS_GSI_AUTHZ_ERROR_CALLOUT = 3 }

2.2.1 Enumeration Type Documentation

2.2.1.1 enum `globus_gsi_authz_error_t`

GSI Authz Error codes.

Enumeration values:

- GLOBUS_GSI_AUTHZ_ERROR_SUCCESS** Success.
- GLOBUS_GSI_AUTHZ_ERROR_ERRNO** Error with system call.
- GLOBUS_GSI_AUTHZ_ERROR_BAD_PARAMETER** Invalid parameter.
- GLOBUS_GSI_AUTHZ_ERROR_CALLOUT** Callout returned an error.

Index

globus_gsi_authorize
 globus_gsi_authz, 2

globus_gsi_authz
 globus_gsi_authorize, 2
 globus_gsi_authz_get_authorization_identity,
 2
 globus_gsi_authz_handle_destroy, 2
 globus_gsi_authz_handle_init, 1

globus_gsi_authz_constants
 GLOBUS_GSI_AUTHZ_ERROR_BAD_-
 PARAMETER, 3
 GLOBUS_GSI_AUTHZ_ERROR_-
 CALLOUT, 3
 GLOBUS_GSI_AUTHZ_ERROR_ERRNO, 3
 GLOBUS_GSI_AUTHZ_ERROR_SUCCESS,
 3
 globus_gsi_authz_error_t, 3

GLOBUS_GSI_AUTHZ_ERROR_BAD_-
 PARAMETER
 globus_gsi_authz_constants, 3

GLOBUS_GSI_AUTHZ_ERROR_CALLOUT
 globus_gsi_authz_constants, 3

GLOBUS_GSI_AUTHZ_ERROR_ERRNO
 globus_gsi_authz_constants, 3

GLOBUS_GSI_AUTHZ_ERROR_SUCCESS
 globus_gsi_authz_constants, 3

globus_gsi_authz_error_t
 globus_gsi_authz_constants, 3

globus_gsi_authz_get_authorization_identity
 globus_gsi_authz, 2

globus_gsi_authz_handle_destroy
 globus_gsi_authz, 2

globus_gsi_authz_handle_init
 globus_gsi_authz, 1

GSI Authorization API, 1

GSI Credential Constants, 3