

globus gsi credential
6.0

Generated by Doxygen 1.8.3.1

Thu Dec 5 2013 06:40:59

Contents

1	Globus GSI Credential	1
2	Module Index	1
2.1	Modules	2
3	Module Documentation	2
3.1	Credential Constants	2
3.1.1	Detailed Description	2
3.1.2	Enumeration Type Documentation	2
3.2	Activation	4
3.2.1	Detailed Description	4
3.2.2	Macro Definition Documentation	4
3.3	Credential Handle Management	5
3.3.1	Detailed Description	7
3.3.2	Typedef Documentation	7
3.3.3	Function Documentation	7
3.4	Credential Handle Attributes	15
3.4.1	Detailed Description	15
3.4.2	Typedef Documentation	15
3.4.3	Function Documentation	16
3.5	Credential Operations	19
3.5.1	Detailed Description	19
3.5.2	Function Documentation	20
	Index	24

1 Globus GSI Credential

The Globus GSI Credential library. This library contains functions that provide support for handling X.509 based PKI credentials

- **Activation** (p. 4)
- **Credential Handle Management** (p. 5)
- **Credential Handle Attributes** (p. 15)
- **Credential Operations** (p. 19)
- **Credential Constants** (p. 2)

2 Module Index

2.1 Modules

Here is a list of all modules:

Credential Constants	2
Activation	4
Credential Handle Management	5
Credential Handle Attributes	15
Credential Operations	19

3 Module Documentation

3.1 Credential Constants

Enumerations

- enum **globus_gsi_cred_error_t** {
 GLOBUS_GSI_CRED_ERROR_SUCCESS = 0,
 GLOBUS_GSI_CRED_ERROR_READING_PROXY_CRED = 1,
 GLOBUS_GSI_CRED_ERROR_READING_HOST_CRED = 2,
 GLOBUS_GSI_CRED_ERROR_READING_SERVICE_CRED = 3,
 GLOBUS_GSI_CRED_ERROR_READING_CRED = 4,
 GLOBUS_GSI_CRED_ERROR_WRITING_CRED = 5,
 GLOBUS_GSI_CRED_ERROR_WRITING_PROXY_CRED = 6,
 GLOBUS_GSI_CRED_ERROR_CHECKING_PROXY = 7,
 GLOBUS_GSI_CRED_ERROR_VERIFYING_CRED = 8,
 GLOBUS_GSI_CRED_ERROR_WITH_CRED = 9,
 GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT = 10,
 GLOBUS_GSI_CRED_ERROR_WITH_CRED_PRIVATE_KEY = 11,
 GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_CHAIN = 12,
 GLOBUS_GSI_CRED_ERROR_ERRNO = 13,
 GLOBUS_GSI_CRED_ERROR_SYSTEM_CONFIG = 14,
 GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS = 15,
 GLOBUS_GSI_CRED_ERROR_WITH_SSL_CTX = 16,
 GLOBUS_GSI_CRED_ERROR_WITH_CALLBACK_DATA = 17,
 GLOBUS_GSI_CRED_ERROR_CREATING_ERROR_OBJ = 18,
 GLOBUS_GSI_CRED_ERROR_KEY_IS_PASS_PROTECTED = 19,
 GLOBUS_GSI_CRED_ERROR_NO_CRED_FOUND = 20,
 GLOBUS_GSI_CRED_ERROR_SUBJECT_CMP = 21,
 GLOBUS_GSI_CRED_ERROR_GETTING_SERVICE_NAME = 22,
 GLOBUS_GSI_CRED_ERROR_BAD_PARAMETER = 23,
 GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_NAME = 24,
 GLOBUS_GSI_CRED_ERROR_LAST = 25 }
• enum **globus_gsi_cred_type_t**

3.1.1 Detailed Description

3.1.2 Enumeration Type Documentation

3.1.2.1 enum globus_gsi_cred_error_t

Credential Error codes.

Enumerator

GLOBUS_GSI_CRED_ERROR_SUCCESS Success - never used.

GLOBUS_GSI_CRED_ERROR_READING_PROXY_CRED Failed to read proxy credential.

GLOBUS_GSI_CRED_ERROR_READING_HOST_CRED Failed to read host credential.

GLOBUS_GSI_CRED_ERROR_READING_SERVICE_CRED Failed to read service credential.

GLOBUS_GSI_CRED_ERROR_READING_CRED Failed to read user credential.

GLOBUS_GSI_CRED_ERROR_WRITING_CRED Failed to write credential.

GLOBUS_GSI_CRED_ERROR_WRITING_PROXY_CRED Failed to write proxy credential.

GLOBUS_GSI_CRED_ERROR_CHECKING_PROXY Error checking for proxy credential.

GLOBUS_GSI_CRED_ERROR_VERIFYING_CRED Failed to verify credential.

GLOBUS_GSI_CRED_ERROR_WITH_CRED Invalid credential.

GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT Invalid certificate.

GLOBUS_GSI_CRED_ERROR_WITH_CRED_PRIVATE_KEY Invalid private key.

GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_CHAIN Invalid certificate chain.

GLOBUS_GSI_CRED_ERROR_ERRNO System error.

GLOBUS_GSI_CRED_ERROR_SYSTEM_CONFIG A Globus GSI System Configuration call failed.

GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS Invalid credential handle attributes.

GLOBUS_GSI_CRED_ERROR_WITH_SSL_CTX Faulty SSL context.

GLOBUS_GSI_CRED_ERROR_WITH_CALLBACK_DATA Faulty callback data.

GLOBUS_GSI_CRED_ERROR_CREATING_ERROR_OBJ Failed to aggregate errors.

GLOBUS_GSI_CRED_ERROR_KEY_IS_PASS_PROTECTED Error reading private key - the key is password protected.

GLOBUS_GSI_CRED_ERROR_NO_CRED_FOUND Couldn't find credential to read.

GLOBUS_GSI_CRED_ERROR_SUBJECT_CMP Credential subjects do not compare.

GLOBUS_GSI_CRED_ERROR_GETTING_SERVICE_NAME Unable to obtain service name from CN entry.

GLOBUS_GSI_CRED_ERROR_BAD_PARAMETER Invalid function parameter.

GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_NAME Failed to process certificate subject.

GLOBUS_GSI_CRED_ERROR_LAST End marker - never used.

3.1.2.2 enum globus_gsi_cred_type_t

Credential Type

An enum representing a GSI Credential Type which holds info about the type of a particular credential.

The three types of credential can be: GLOBUS_PROXY, GLOBUS_USER, or GLOBUS_HOST.

See Also

Credential Handle Management (p. 5)

3.2 Activation

Macros

- `#define GLOBUS_GSI_CREDENTIAL_MODULE`

3.2.1 Detailed Description

Globus GSI Credential uses standard Globus module activation and deactivation. Before any Globus GSI Credential functions are called, the following function must be called:

```
globus_module_activate(GLOBUS_GSI_CREDENTIAL_MODULE)
```

This function returns `GLOBUS_SUCCESS` if Globus GSI Credential was successfully initialized, and you are therefore allowed to subsequently call Globus GSI Credential functions. Otherwise, an error code is returned, and Globus GSI Credential functions should not be subsequently called. This function may be called multiple times.

To deactivate Globus GSI Credential, the following function must be called:

```
globus_module_deactivate(GLOBUS_GSI_CREDENTIAL_MODULE)
```

This function should be called once for each time Globus GSI Credential was activated.

3.2.2 Macro Definition Documentation

3.2.2.1 `#define GLOBUS_GSI_CREDENTIAL_MODULE`

Module descriptor.

3.3 Credential Handle Management

Typedefs

- typedef struct
globus_l_gsi_cred_handle_s * **globus_gsi_cred_handle_t**

Initializing and Destroying a Handle

- globus_result_t **globus_gsi_cred_handle_init** (globus_gsi_cred_handle_t *handle, **globus_gsi_cred_handle_attrs_t** handle_attrs)
- globus_result_t **globus_gsi_cred_handle_destroy** (globus_gsi_cred_handle_t handle)

Copying a Handle

- globus_result_t **globus_gsi_cred_handle_copy** (globus_gsi_cred_handle_t source, **globus_gsi_cred_handle_t** *dest)

Getting the Handle Attributes

- globus_result_t **globus_gsi_cred_get_handle_attrs** (globus_gsi_cred_handle_t handle, **globus_gsi_cred_handle_attrs_t** *attrs)

Getting the Credential Expiration

- globus_result_t **globus_gsi_cred_get_goodtill** (globus_gsi_cred_handle_t cred_handle, time_t *goodtill)

Getting the Credential Lifetime

- globus_result_t **globus_gsi_cred_get_lifetime** (globus_gsi_cred_handle_t cred_handle, time_t *lifetime)

Getting the Credential Strength

- globus_result_t **globus_gsi_cred_get_key_bits** (globus_gsi_cred_handle_t cred_handle, int *key_bits)

Setting and Getting the Certificate

- globus_result_t **globus_gsi_cred_set_cert** (globus_gsi_cred_handle_t handle, X509 *cert)
- globus_result_t **globus_gsi_cred_get_cert** (globus_gsi_cred_handle_t handle, X509 **cert)

Setting and Getting the Credential Key

- globus_result_t **globus_gsi_cred_set_key** (globus_gsi_cred_handle_t handle, EVP_PKEY *key)
- globus_result_t **globus_gsi_cred_get_key** (globus_gsi_cred_handle_t handle, EVP_PKEY **key)

Setting and Getting the Certificate Chain

- globus_result_t **globus_gsi_cred_set_cert_chain** (globus_gsi_cred_handle_t handle, STACK_OF(X509)*cert_chain)
- globus_result_t **globus_gsi_cred_get_cert_chain** (globus_gsi_cred_handle_t handle, STACK_OF(X509)**cert_chain)

Get Cred Cert X509 Subject Name object

- globus_result_t **globus_gsi_cred_get_X509_subject_name** (globus_gsi_cred_handle_t handle, X509_NAME **subject_name)

Get X509 Identity Name

- globus_result_t **globus_gsi_cred_get_X509_identity_name** (globus_gsi_cred_handle_t handle, X509_NAME **identity_name)

Get Cred Cert Subject Name

- globus_result_t **globus_gsi_cred_get_subject_name** (globus_gsi_cred_handle_t handle, char **subject_name)

Get Policies from Cert Chain

- globus_result_t **globus_gsi_cred_get_policies** (globus_gsi_cred_handle_t handle, STACK **policies)

Get Policy Languages from Cert Chain

- globus_result_t **globus_gsi_cred_get_policy_languages** (globus_gsi_cred_handle_t handle, STACK_OF(ASN1_OBJECT) **policy_languages)

Get Cred Cert X509 Issuer Name object

- globus_result_t **globus_gsi_cred_get_X509_issuer_name** (globus_gsi_cred_handle_t handle, X509_NAME **issuer_name)

Get Issuer Name

- globus_result_t **globus_gsi_cred_get_issuer_name** (globus_gsi_cred_handle_t handle, char **issuer_name)

Get Identity Name

- globus_result_t **globus_gsi_cred_get_identity_name** (globus_gsi_cred_handle_t handle, char **identity_name)

Credential validation functions

- globus_result_t **globus_gsi_cred_verify_cert_chain** (globus_gsi_cred_handle_t cred_handle, globus_gsi_callback_data_t callback_data)
- globus_result_t **globus_gsi_cred_verify_cert_chain_when** (globus_gsi_cred_handle_t cred_handle, globus_gsi_callback_data_t callback_data_in, time_t check_time)
- globus_result_t **globus_gsi_cred_verify** (globus_gsi_cred_handle_t handle)

3.3.1 Detailed Description

Create/Destroy/Modify a GSI Credential Handle. Within the Globus GSI Credential Library, all credential operations require a handle parameter. Currently only one operation may be in progress at once per credential handle.

This section defines operations to create, modify and destroy GSI Credential handles.

3.3.2 Typedef Documentation

3.3.2.1 `typedef struct globus_l_gsi_cred_handle_s* globus_gsi_cred_handle_t`

GSI Credential Handle.

A GSI Credential handle keeps track of state relating to a credential. Handles can have immutable **attributes** (p. 15) associated with them. All credential **operations** (p. 19) take a credential handle pointer as a parameter.

See Also

`globus_gsi_cred_handle_init()` (p. 7), `globus_gsi_cred_handle_destroy()` (p. 7), `globus_gsi_cred_handle_attrs_t` (p. 15)

3.3.3 Function Documentation

3.3.3.1 `globus_result_t globus_gsi_cred_handle_init (globus_gsi_cred_handle_t * handle, globus_gsi_cred_handle_attrs_t handle_attrs)`

Initializes a credential handle to be used credential handling functions.

Takes a set of handle attributes that are immutable to the handle. The handle attributes are only pointed to by the handle, so the lifetime of the attributes needs to be as long as that of the handle.

Parameters

<i>handle</i>	The handle to be initialized
<i>handle_attrs</i>	The immutable attributes of the handle

Returns

GLOBUS_SUCCESS or an error captured in a `globus_result_t`

References GLOBUS_GSI_CRED_ERROR_BAD_PARAMETER, GLOBUS_GSI_CRED_ERROR_ERRNO, GLOBUS_GSI_CRED_ERROR_WITH_CRED, `globus_gsi_cred_handle_attrs_copy()`, `globus_gsi_cred_handle_attrs_init()`, and GLOBUS_GSI_CREDENTIAL_MODULE.

3.3.3.2 `globus_result_t globus_gsi_cred_handle_destroy (globus_gsi_cred_handle_t handle)`

Destroys the credential handle.

Parameters

<i>handle</i>	The credential handle to be destroyed
---------------	---------------------------------------

Returns

GLOBUS_SUCCESS

References `globus_gsi_cred_handle_attrs_destroy()`.

3.3.3.3 `globus_result_t globus_gsi_cred_handle_copy (globus_gsi_cred_handle_t source, globus_gsi_cred_handle_t * dest)`

Copies a credential handle.

Parameters

<i>source</i>	The handle to be copied
<i>dest</i>	The destination of the copy

Returns

GLOBUS_SUCCESS or an error captured in a `globus_result_t`

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and `globus_gsi_cred_handle_init()`.

3.3.3.4 `globus_result_t globus_gsi_cred_get_handle_attrs (globus_gsi_cred_handle_t handle, globus_gsi_cred_handle_attrs_t * attrs)`

This function retrieves a copy of the credential handle attributes.

Parameters

<i>handle</i>	The credential handle to retrieve the attributes from
<i>attrs</i>	Contains the credential attributes on return

Returns

GLOBUS_SUCCESS or an error captured in a `globus_result_t`

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and `globus_gsi_cred_handle_attrs_copy()`.

3.3.3.5 `globus_result_t globus_gsi_cred_get_goodtill (globus_gsi_cred_handle_t cred_handle, time_t * goodtill)`

This function retrieves the expiration time of the credential contained in the handle.

Parameters

<i>cred_handle</i>	The credential handle to retrieve the expiration time from
<i>goodtill</i>	Contains the expiration time on return

Returns

GLOBUS_SUCCESS or an error captured in a `globus_result_t`

References GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.3.3.6 `globus_result_t globus_gsi_cred_get_lifetime (globus_gsi_cred_handle_t cred_handle, time_t * lifetime)`

This function retrieves the lifetime of the credential contained in a handle.

Parameters

<i>cred_handle</i>	The credential handle to retrieve the lifetime from
<i>lifetime</i>	Contains the lifetime on return

Returns

GLOBUS_SUCCESS or an error captured in a globus_result_t

References GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.3.3.7 globus_result_t globus_gsi_cred_get_key_bits (globus_gsi_cred_handle_t cred_handle, int * key_bits)

This function retrieves the key strength of the credential contained in a handle.

Parameters

<i>cred_handle</i>	The credential handle to retrieve the strength from
<i>key_bits</i>	Contains the number of bits in the key on return

Returns

GLOBUS_SUCCESS or an error captured in a globus_result_t

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT.

3.3.3.8 globus_result_t globus_gsi_cred_set_cert (globus_gsi_cred_handle_t handle, X509 * cert)

Set the Credential's Certificate.

The X509 cert that is passed in should be a valid X509 certificate object

Parameters

<i>handle</i>	The credential handle to set the certificate on
<i>cert</i>	The X509 cert to set in the cred handle. The cert passed in can be NULL which will set the cert in the handle to NULL, freeing the current cert in the handle.

Returns

GLOBUS_SUCCESS or an error object id if an error

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT.

3.3.3.9 globus_result_t globus_gsi_cred_get_cert (globus_gsi_cred_handle_t handle, X509 ** cert)

Get the certificate of a credential.

Parameters

<i>handle</i>	The credential handle to get the certificate from
<i>cert</i>	The resulting X509 certificate, a duplicate of the certificate in the credential handle. This variable should be freed when the user is finished with it using the function X509_free.

Returns

GLOBUS_SUCCESS if no error, otherwise an error object id is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.3.3.10 `globus_result_t globus_gsi_cred_set_key (globus_gsi_cred_handle_t handle, EVP_PKEY * key)`

Set the private key of the credential handle.

Parameters

<i>handle</i>	The handle on which to set the key.
<i>key</i>	The private key to set the handle's key to. This value can be NULL, in which case the current handle's key is freed.

References GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.3.3.11 `globus_result_t globus_gsi_cred_get_key (globus_gsi_cred_handle_t handle, EVP_PKEY ** key)`

Get the credential handle's private key.

Parameters

<i>handle</i>	The credential handle containing the private key to get
<i>key</i>	The private key which after this function returns is set to a duplicate of the private key of the credential handle. This variable needs to be freed by the user when it is no longer used via the function <code>EVP_PKEY_free</code> .

Returns

GLOBUS_SUCCESS or an error object identifier

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_PRIVATE_KEY.

3.3.3.12 `globus_result_t globus_gsi_cred_set_cert_chain (globus_gsi_cred_handle_t handle, STACK_OF(X509)* cert_chain)`

Set the certificate chain of the credential handle.

Parameters

<i>handle</i>	The handle containing the certificate chain field to set
<i>cert_chain</i>	The certificate chain to set the handle's certificate chain to

Returns

GLOBUS_SUCCESS if no error, otherwise an error object id is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_CHAIN.

3.3.3.13 `globus_result_t globus_gsi_cred_get_cert_chain (globus_gsi_cred_handle_t handle, STACK_OF(X509)** cert_chain)`

Get the certificate chain of the credential handle.

Parameters

<i>handle</i>	The credential handle containing the certificate chain to get
<i>cert_chain</i>	The certificate chain to set as a duplicate of the cert chain in the credential handle. This variable (or the variable it points to) needs to be freed when the user is finished with it using <code>sk_X509_free</code> .

Returns

GLOBUS_SUCCESS if no error, otherwise an error object id is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_CHAIN.

3.3.3.14 `globus_result_t globus_gsi_cred_get_X509_subject_name (globus_gsi_cred_handle_t handle, X509_NAME ** subject_name)`

Get the credential handle's certificate subject name.

Parameters

<i>handle</i>	The credential handle containing the certificate to get the subject name of
<i>subject_name</i>	The subject name as an X509_NAME object. This should be freed using X509_NAME_free when the user is finished with it

Returns

GLOBUS_SUCCESS if no error, a error object id otherwise

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT.

3.3.3.15 `globus_result_t globus_gsi_cred_get_X509_identity_name (globus_gsi_cred_handle_t handle, X509_NAME ** identity_name)`

Get the identity's X509 subject name from the credential handle.

Parameters

<i>handle</i>	The credential handle containing the certificate to get the identity from
<i>identity_name</i>	The identity certificate's X509 subject name

Returns

GLOBUS_SUCCESS if no error, otherwise an error object identifier is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.3.3.16 `globus_result_t globus_gsi_cred_get_subject_name (globus_gsi_cred_handle_t handle, char ** subject_name)`

Get the credential handle's certificate subject name.

Parameters

<i>handle</i>	The credential handle containing the certificate to get the subject name of
<i>subject_name</i>	The subject name as a string. This should be freed using free() when the user is finished with it

Returns

GLOBUS_SUCCESS if no error, a error object id otherwise

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and globus_gsi_cred_get_X509_subject_name().

3.3.3.17 globus_result_t globus_gsi_cred_get_policies (globus_gsi_cred_handle_t handle, STACK ** policies)

Get the Policies from the Cert Chain in the handle.

The policies will be null-terminated as they are added to the handle. If a policy for a cert in the chain doesn't exist, the string in the stack will be set to the static string GLOBUS_NULL_POLICIES

Parameters

<i>handle</i>	the handle to get the cert chain containing the policies
<i>policies</i>	the stack of policies retrieved from the handle's cert chain

Returns

GLOBUS_SUCCESS or an error object if an error occurred

References GLOBUS_GSI_CRED_ERROR_ERRNO, GLOBUS_GSI_CRED_ERROR_WITH_CRED, GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_CHAIN, and GLOBUS_GSI_CREDENTIAL_MODULE.

3.3.3.18 globus_result_t globus_gsi_cred_get_policy_languages (globus_gsi_cred_handle_t handle, STACK_OF(ASN1_OBJECT)** policy_languages)

Get the policy languages from the cert chain in the handle.

Parameters

<i>handle</i>	the handle to get the cert chain containing the policies
<i>policy_languages</i>	the stack of policies retrieved from the handle's cert chain

Returns

GLOBUS_SUCCESS or an error object if an error occurred

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_CHAIN.

3.3.3.19 globus_result_t globus_gsi_cred_get_X509_issuer_name (globus_gsi_cred_handle_t handle, X509_NAME ** issuer_name)

Get the credential handle's certificate issuer name.

Parameters

<i>handle</i>	The credential handle containing the certificate to get the issuer name of
<i>issuer_name</i>	The issuer name as an X509_NAME object. This should be freed using X509_NAME_free when the user is finished with it

Returns

GLOBUS_SUCCESS if no error, a error object id otherwise

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT.

3.3.3.20 globus_result_t globus_gsi_cred_get_issuer_name (globus_gsi_cred_handle_t handle, char ** issuer_name)

Get the issuer's subject name from the credential handle.

Parameters

<i>handle</i>	The credential handle containing the certificate to get the issuer of
<i>issuer_name</i>	The issuer certificate's subject name

Returns

GLOBUS_SUCCESS if no error, otherwise an error object identifier is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT.

3.3.3.21 `globus_result_t globus_gsi_cred_get_identity_name (globus_gsi_cred_handle_t handle, char ** identity_name)`

Get the identity's subject name from the credential handle.

Parameters

<i>handle</i>	The credential handle containing the certificate to get the identity of
<i>identity_name</i>	The identity certificate's subject name

Returns

GLOBUS_SUCCESS if no error, otherwise an error object identifier is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED, GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_NAME, and `globus_gsi_cred_get_X509_identity_name()`.

3.3.3.22 `globus_result_t globus_gsi_cred_verify_cert_chain (globus_gsi_cred_handle_t cred_handle, globus_gsi_callback_data_t callback_data)`

This function performs path validation on the certificate chain contained in the credential handle.

Parameters

<i>cred_handle</i>	The credential handle containing the certificate chain to be validated
<i>callback_data</i>	A initialized callback data structure

Returns

GLOBUS_SUCCESS if no error, otherwise an error object identifier is returned

References GLOBUS_GSI_CRED_ERROR_VERIFYING_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CALLBACK_DATA.

3.3.3.23 `globus_result_t globus_gsi_cred_verify_cert_chain_when (globus_gsi_cred_handle_t cred_handle, globus_gsi_callback_data_t callback_data_in, time_t check_time)`

This function performs path validation on the certificate chain contained in the credential handle.

Expiration checks are done at the time given.

Parameters

<i>cred_handle</i>	The credential handle containing the certificate chain to be validated
<i>callback_data</i>	A callback data structure. If NULL, one will be initialized with only the default cert dir set.
<i>check_time</i>	Check if the cert chain was valid at this time. Set to 0 to use a time that the cert is valid, essentially bypassing the expiration check.

Returns

GLOBUS_SUCCESS if no error, otherwise an error object identifier is returned

References GLOBUS_GSI_CRED_ERROR_VERIFYING_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CALLBACK_DATA.

3.3.3.24 globus_result_t globus_gsi_cred_verify (globus_gsi_cred_handle_t handle)

This function checks that the certificate is signed by the public key of the issuer cert (the first cert in the chain).

Note that this function DOES NOT check the private key or the public of the certificate, as stated in a previous version of the documentation.

Parameters

<i>handle</i>	The credential handle containing the certificate and key to be validated
---------------	--

Returns

GLOBUS_SUCCESS if no error, otherwise an error object identifier is returned

References GLOBUS_GSI_CRED_ERROR_VERIFYING_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT_CHAIN.

3.4 Credential Handle Attributes

Typedefs

- typedef struct
globus_l_gsi_cred_handle_attrs_s * **globus_gsi_cred_handle_attrs_t**

Credential Handle Attributes Initialization and Destruction

- globus_result_t **globus_gsi_cred_handle_attrs_init** (globus_gsi_cred_handle_attrs_t *handle_attrs)
- globus_result_t **globus_gsi_cred_handle_attrs_destroy** (globus_gsi_cred_handle_attrs_t handle_attrs)

Copy Credential Handle Attributes

- globus_result_t **globus_gsi_cred_handle_attrs_copy** (globus_gsi_cred_handle_attrs_t source, globus_gsi_cred_handle_attrs_t *dest)

Setting and Getting the CA Cert Dir

- globus_result_t **globus_gsi_cred_handle_attrs_set_ca_cert_dir** (globus_gsi_cred_handle_attrs_t handle_attrs, char *ca_cert_dir)
- globus_result_t **globus_gsi_cred_handle_attrs_get_ca_cert_dir** (globus_gsi_cred_handle_attrs_t handle_attrs, char **ca_cert_dir)

Setting and Getting the Search Order

- globus_result_t **globus_gsi_cred_handle_attrs_set_search_order** (globus_gsi_cred_handle_attrs_t handle_attrs, globus_gsi_cred_type_t search_order[])
- globus_result_t **globus_gsi_cred_handle_attrs_get_search_order** (globus_gsi_cred_handle_attrs_t handle_attrs, globus_gsi_cred_type_t **search_order)

3.4.1 Detailed Description

Create/Destroy/Modify GSI Credential Handle Attributes. Within the Globus GSI Credential Library, all credential handles contain an attribute structure, which in turn contains handle instance independent attributes.

This section defines operations to create, modify and destroy GSI Credential handle attributes.

3.4.2 Typedef Documentation

3.4.2.1 typedef struct globus_l_gsi_cred_handle_attrs_s* globus_gsi_cred_handle_attrs_t

Credential Handle Attributes.

Credential handle attributes provide a set of immutable parameters for a credential handle

See Also

globus_gsi_cred_handle_init (p. 7)

3.4.3 Function Documentation

3.4.3.1 `globus_result_t globus_gsi_cred_handle_attrs_init (globus_gsi_cred_handle_attrs_t * handle_attrs)`

Initializes the immutable Credential Handle Attributes. The handle attributes are initialized as follows:

- The search order is set to SERVICE, HOST, PROXY, USER
- All other attributes are set to 0/NULL

Parameters

<i>handle_attrs</i>	the attributes to be initialized
---------------------	----------------------------------

Returns

GLOBUS_SUCCESS if initialization was successful, otherwise an error is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS.

3.4.3.2 `globus_result_t globus_gsi_cred_handle_attrs_destroy (globus_gsi_cred_handle_attrs_t handle_attrs)`

Destroy the Credential Handle Attributes.

This function does some cleanup and deallocation of the handle attributes.

Parameters

<i>handle_attrs</i>	The handle attributes to destroy
---------------------	----------------------------------

Returns

GLOBUS_SUCCESS

3.4.3.3 `globus_result_t globus_gsi_cred_handle_attrs_copy (globus_gsi_cred_handle_attrs_t source, globus_gsi_cred_handle_attrs_t * dest)`

Copy the Credential Handle Attributes.

Parameters

<i>source</i>	The handle attribute to be copied
<i>dest</i>	The copy

Returns

GLOBUS_SUCCESS unless there was an error, in which case an error object is returned.

References GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS, `globus_gsi_cred_handle_attrs_destroy()`, and `globus_gsi_cred_handle_attrs_init()`.

3.4.3.4 `globus_result_t globus_gsi_cred_handle_attrs_set_ca_cert_dir (globus_gsi_cred_handle_attrs_t handle_attrs, char * ca_cert_dir)`

Set the Trusted CA Certificate Directory Location.

Parameters

<i>handle_attrs</i>	the credential handle attributes to set
<i>ca_cert_dir</i>	the trusted ca certificates directory

Returns

GLOBUS_SUCCESS if no errors occurred. In case of a null *handle_attrs*, an error object id is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS.

3.4.3.5 `globus_result_t globus_gsi_cred_handle_attrs_get_ca_cert_dir (globus_gsi_cred_handle_attrs_t handle_attrs, char ** ca_cert_dir)`

Get the trusted ca cert directory.

Parameters

<i>handle_attrs</i>	the credential handle attributes to get the trusted ca cert directory from
<i>ca_cert_dir</i>	the trusted ca certificates directory

Returns

GLOBUS_SUCCESS if no errors occurred. In case of a null *handle_attrs* or pointer to *ca_cert_dir*, an error object id is returned

References GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS.

3.4.3.6 `globus_result_t globus_gsi_cred_handle_attrs_set_search_order (globus_gsi_cred_handle_attrs_t handle_attrs, globus_gsi_cred_type_t search_order[])`

Set the search order for finding a user certificate.

The default value is {SERVICE, HOST, PROXY, USER}

Parameters

<i>handle_attrs</i>	The handle attributes to set the search order of
<i>search_order</i>	The search order. Should be a three element array containing in some order PROXY, USER, HOST, SERVICE. The array should be terminated by the value GLOBUS_SO_END.

Returns

GLOBUS_SUCCESS unless *handle_attrs* is null

References GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS.

3.4.3.7 `globus_result_t globus_gsi_cred_handle_attrs_get_search_order (globus_gsi_cred_handle_attrs_t handle_attrs, globus_gsi_cred_type_t ** search_order)`

Get the search order of the handle attributes.

Parameters

<i>handle_attrs</i>	The handle attributes to get the search order from
<i>search_order</i>	The search_order of the handle attributes

Returns

GLOBUS_SUCCESS unless handle_attrs is null

References GLOBUS_GSI_CRED_ERROR_WITH_CRED_HANDLE_ATTRS.

3.5 Credential Operations

Read Credential

- globus_result_t **globus_gsi_cred_read** (globus_gsi_cred_handle_t handle, X509_NAME *desired_subject)

Reading Proxy Credentials

- globus_result_t **globus_gsi_cred_read_proxy** (globus_gsi_cred_handle_t handle, const char *proxy_filename)
- globus_result_t **globus_gsi_cred_read_proxy_bio** (globus_gsi_cred_handle_t handle, BIO *bio)

Read Key

- globus_result_t **globus_gsi_cred_read_key** (globus_gsi_cred_handle_t handle, char *key_filename, int(*pw_cb)())

Read Cert and chain from file

- globus_result_t **globus_gsi_cred_read_cert** (globus_gsi_cred_handle_t handle, char *cert_filename)

Read Cert and chain from BIO stream

- globus_result_t **globus_gsi_cred_read_cert_bio** (globus_gsi_cred_handle_t handle, BIO *bio)

Read Cert and chain from a buffer

- globus_result_t **globus_gsi_cred_read_cert_buffer** (char *pem_buf, globus_gsi_cred_handle_t *out_handle, X509 **out_cert, STACK_OF(X509) **out_cert_chain, char **out_subject)

Read Cert & Key in PKCS12 Format

- globus_result_t **globus_gsi_cred_read_pkcs12** (globus_gsi_cred_handle_t handle, char *pkcs12_filename)

Write Credential

- globus_result_t **globus_gsi_cred_write** (globus_gsi_cred_handle_t handle, BIO *bio)
- globus_result_t **globus_gsi_cred_write_proxy** (globus_gsi_cred_handle_t handle, char *proxy_filename)

Get the X509 certificate type (EEC, CA, proxy type, etc.)

- globus_result_t **globus_gsi_cred_get_cert_type** (globus_gsi_cred_handle_t handle, globus_gsi_cert_utils_cert_type_t *type)

3.5.1 Detailed Description

Read/Write a GSI Credential Handle. This section defines operations to read and write GSI Credential handles.

3.5.2 Function Documentation

3.5.2.1 `globus_result_t globus_gsi_cred_read (globus_gsi_cred_handle_t handle, X509_NAME * desired_subject)`

Read a Credential from a filesystem location.

The credential to read will be determined by the search order specified in the handle attributes.

Parameters

<i>handle</i>	The credential handle to set. This credential handle should already be initialized using <code>globus_gsi_cred_handle_init</code> .
<i>desired_subject</i>	The subject to check for when reading in a credential. The <code>desired_subject</code> should be either a exact match of the read cert's subject or should just contain the /CN entry. If null, the credential read in is the first match based on the system configuration (paths and environment variables)

Returns

GLOBUS_SUCCESS if no errors occurred, otherwise, an error object identifier is returned.

See Also

`globus_gsi_cred_read_proxy()` (p. 20)
`globus_gsi_cred_read_cert_and_key()`

Note

This function always searches for the desired credential. If you don't want to perform a search, then don't use this function. The search goes in the order of the handle attributes' search order.

References GLOBUS_GSI_CRED_ERROR_KEY_IS_PASS_PROTECTED, GLOBUS_GSI_CRED_ERROR_NO_CRED_FOUND, GLOBUS_GSI_CRED_ERROR_READING_CRED, GLOBUS_GSI_CRED_ERROR_READING_HOST_CRED, GLOBUS_GSI_CRED_ERROR_READING_PROXY_CRED, GLOBUS_GSI_CRED_ERROR_READING_SERVICE_CRED, GLOBUS_GSI_CRED_ERROR_WITH_CRED, `globus_gsi_cred_get_lifetime()`, `globus_gsi_cred_get_X509_subject_name()`, `globus_gsi_cred_read_cert()`, `globus_gsi_cred_read_key()`, `globus_gsi_cred_read_proxy()`, and GLOBUS_GSI_CREDENTIAL_MODULE.

3.5.2.2 `globus_result_t globus_gsi_cred_read_proxy (globus_gsi_cred_handle_t handle, const char * proxy_filename)`

Read a proxy from a PEM file.

Parameters

<i>handle</i>	The credential handle to set based on the proxy credential read from the file
<i>proxy_filename</i>	The file containing the proxy credential

Returns

GLOBUS_SUCCESS or an error object identifier

References GLOBUS_GSI_CRED_ERROR_READING_PROXY_CRED, and `globus_gsi_cred_read_proxy_bio()`.

3.5.2.3 `globus_result_t globus_gsi_cred_read_proxy_bio (globus_gsi_cred_handle_t handle, BIO * bio)`

Read a Proxy Credential from a BIO stream and set the credential handle to represent the read credential.

The values read from the stream, in order, will be the signed certificate, the private key, and the certificate chain

Parameters

<i>handle</i>	The credential handle to set. The credential should handle be initialized (i.e. not NULL).
<i>bio</i>	The stream to read the credential from

Returns

GLOBUS_SUCCESS unless an error occurred, in which case an error object is returned

References GLOBUS_GSI_CRED_ERROR_READING_PROXY_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.5.2.4 `globus_result_t globus_gsi_cred_read_key (globus_gsi_cred_handle_t handle, char * key_filename, int(*)() pw_cb)`

Read a key from a PEM file.

Parameters

<i>handle</i>	the handle to set based on the key that is read
<i>key_filename</i>	the filename of the key to read
<i>pw_cb</i>	the callback for obtaining a password for decrypting the key.

Returns

GLOBUS_SUCCESS or an error object identifier

References GLOBUS_GSI_CRED_ERROR_KEY_IS_PASS_PROTECTED, and GLOBUS_GSI_CRED_ERROR_READING_CRED.

3.5.2.5 `globus_result_t globus_gsi_cred_read_cert (globus_gsi_cred_handle_t handle, char * cert_filename)`

Read a cert from a file.

Cert should be in PEM format. Will also read additional certificates as chain if present.

Parameters

<i>handle</i>	the handle to set based on the certificate that is read
<i>cert_filename</i>	the filename of the certificate to read

Returns

GLOBUS_SUCCESS or an error object identifier

References GLOBUS_GSI_CRED_ERROR_READING_CRED, and globus_gsi_cred_read_cert_bio().

3.5.2.6 `globus_result_t globus_gsi_cred_read_cert_bio (globus_gsi_cred_handle_t handle, BIO * bio)`

Read a cert from a BIO.

Cert should be in PEM format. Will also read additional certificates as chain if present.

Parameters

<i>handle</i>	the handle to set based on the certificate that is read
<i>bio</i>	the bio to read the certificate from

Returns

GLOBUS_SUCCESS or an error object identifier

References GLOBUS_GSI_CRED_ERROR_READING_CRED, GLOBUS_GSI_CRED_ERROR_READING_PROXY_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.5.2.7 `globus_result_t globus_gsi_cred_read_cert_buffer (char * pem_buf, globus_gsi_cred_handle_t * out_handle, X509 ** out_cert, STACK_OF(X509) ** out_cert_chain, char ** out_subject)`

Read a cert from a buffer.

Cert should be in PEM format. Will also read additional certificates as chain if present. Any paramter besides pem_buf may be NULL.

Parameters

<i>pem_buf</i>	The buffer containing the PEM formatted cert and chain.
<i>out_handle</i>	The handle to initialize and set cert on.
<i>out_cert</i>	The X509 certificate. This should be freed with X509_free().
<i>out_cert_chain</i>	The X509 certificate chain. This should be freed with sk_X509_free().
<i>out_subject</i>	The identity name of the cert. This should be freed with OPENSSL_free().

Returns

GLOBUS_SUCCESS or an error object identifier

References GLOBUS_GSI_CRED_ERROR_READING_CRED, globus_gsi_cred_get_cert(), globus_gsi_cred_get_cert_chain(), globus_gsi_cred_get_identity_name(), globus_gsi_cred_handle_destroy(), globus_gsi_cred_handle_init(), and globus_gsi_cred_read_cert_bio().

3.5.2.8 `globus_result_t globus_gsi_cred_read_pkcs12 (globus_gsi_cred_handle_t handle, char * pkcs12_filename)`

Read a cert & key from a file.

The file should be in PKCS12 format.

Parameters

<i>handle</i>	the handle to populate with the read credential
<i>pkcs12_filename</i>	the filename containing the credential to read

Returns

GLOBUS_SUCCESS or an error object identifier

References GLOBUS_GSI_CRED_ERROR_READING_CRED, and GLOBUS_GSI_CRED_ERROR_WITH_CRED.

3.5.2.9 `globus_result_t globus_gsi_cred_write (globus_gsi_cred_handle_t handle, BIO * bio)`

Write out a credential to a BIO.

The credential parameters written, in order, are the signed certificate, the RSA private key, and the certificate chain (a set of X509 certificates). the credential is written out in PEM format.

Parameters

<i>handle</i>	The credential to write out
<i>bio</i>	The BIO stream to write out to

Returns

GLOBUS_SUCCESS unless an error occurred, in which case an error object ID is returned.

References GLOBUS_GSI_CRED_ERROR_WRITING_CRED.

3.5.2.10 globus_result_t globus_gsi_cred_write_proxy (globus_gsi_cred_handle_t handle, char * proxy_filename)

Write out a credential to a file.

The credential parameters written, in order, are the signed certificate, the RSA private key, and the certificate chain (a set of X509 certificates). the credential is written out in PEM format.

Parameters

<i>handle</i>	The credential to write out
<i>proxy_filename</i>	The file to write out to

Returns

GLOBUS_SUCCESS unless an error occurred, in which case an error object ID is returned.

References GLOBUS_GSI_CRED_ERROR_WRITING_PROXY_CRED, and globus_gsi_cred_write().

3.5.2.11 globus_result_t globus_gsi_cred_get_cert_type (globus_gsi_cred_handle_t handle, globus_gsi_cert_utils_cert_type_t * type)

Determine the type of the given X509 certificate For the list of possible values returned, see globus_gsi_cert_utils_cert_type_t.

Parameters

<i>handle</i>	The credential handle containing the certificate
<i>type</i>	The returned X509 certificate type

Returns

GLOBUS_SUCCESS or an error captured in a globus_result_t

References GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT.

Index

Activation, 4

GLOBUS_GSI_CREDENTIAL_MODULE, 4

Credential Constants, 1

GLOBUS_GSI_CRED_ERROR_BAD_PARAMETER, 3

GLOBUS_GSI_CRED_ERROR_CHECKING_PROXY, 2

GLOBUS_GSI_CRED_ERROR_CREATING_ERROR_OBJ, 3

GLOBUS_GSI_CRED_ERROR_ERRNO, 3

GLOBUS_GSI_CRED_ERROR_GETTING_SERVICE_NAME, 3

GLOBUS_GSI_CRED_ERROR_KEY_IS_PROTECTED, 3

GLOBUS_GSI_CRED_ERROR_LAST, 3

GLOBUS_GSI_CRED_ERROR_NO_CREDENTIAL, 3

GLOBUS_GSI_CRED_ERROR_READING_CREDENTIAL, 2

GLOBUS_GSI_CRED_ERROR_READING_HOST_CRED, 2

GLOBUS_GSI_CRED_ERROR_READING_PROXY_CRED, 2

GLOBUS_GSI_CRED_ERROR_READING_SERVICE_CRED, 2

GLOBUS_GSI_CRED_ERROR_SUBJECT_CMP, 3

GLOBUS_GSI_CRED_ERROR_SUCCESS, 2

GLOBUS_GSI_CRED_ERROR_SYSTEM_CONFIG, 3

GLOBUS_GSI_CRED_ERROR_VERIFYING_CREDENTIAL, 2

GLOBUS_GSI_CRED_ERROR_WITH_CALLBACK_DATA, 3

GLOBUS_GSI_CRED_ERROR_WITH_CRED, 2

GLOBUS_GSI_CRED_ERROR_WITH_CREDENTIAL, 2

GLOBUS_GSI_CRED_ERROR_WITH_CREDENTIAL_CHAIN, 3

GLOBUS_GSI_CRED_ERROR_WITH_CREDENTIAL_NAME, 3

GLOBUS_GSI_CRED_ERROR_WITH_CREDENTIAL_ATTRS, 3

GLOBUS_GSI_CRED_ERROR_WITH_CREDENTIAL_PRIVATE_KEY, 2

GLOBUS_GSI_CRED_ERROR_WITH_SSL_CTX, 3

GLOBUS_GSI_CRED_ERROR_WRITING_CREDENTIAL, 2

GLOBUS_GSI_CRED_ERROR_WRITING_PROXY_CRED, 2

globus_gsi_cred_error_t, 2

globus_gsi_cred_type_t, 3

Credential Handle Attributes, 15

globus_gsi_cred_handle_attrs_copy, 16

globus_gsi_cred_handle_attrs_destroy, 16

globus_gsi_cred_handle_attrs_get_ca_cert_dir, 17

globus_gsi_cred_handle_attrs_get_search_order, 17

globus_gsi_cred_handle_attrs_init, 16

globus_gsi_cred_handle_attrs_set_ca_cert_dir, 16

globus_gsi_cred_handle_attrs_set_search_order, 17

globus_gsi_cred_handle_attrs_t, 15

Credential Handle Management, 5

globus_gsi_cred_get_X509_identity_name, 11

globus_gsi_cred_get_X509_issuer_name, 12

globus_gsi_cred_get_X509_subject_name, 11

globus_gsi_cred_get_cert, 9

globus_gsi_cred_get_cert_chain, 10

globus_gsi_cred_get_goodtill, 8

globus_gsi_cred_get_handle_attrs, 8

globus_gsi_cred_get_identity_name, 13

globus_gsi_cred_get_issuer_name, 12

globus_gsi_cred_get_key, 10

globus_gsi_cred_get_key_bits, 9

globus_gsi_cred_get_lifetime, 8

globus_gsi_cred_get_policies, 11

globus_gsi_cred_get_policy_languages, 12

globus_gsi_cred_get_subject_name, 11

globus_gsi_cred_handle_copy, 7

globus_gsi_cred_handle_destroy, 7

globus_gsi_cred_handle_init, 7

globus_gsi_cred_handle_t, 7

globus_gsi_cred_set_cert, 9

globus_gsi_cred_set_cert_chain, 10

globus_gsi_cred_set_key, 9

globus_gsi_cred_verify, 14

globus_gsi_cred_verify_cert_chain, 13

globus_gsi_cred_verify_cert_chain_when, 13

Credential Operations, 19

globus_gsi_cred_get_cert_type, 23

globus_gsi_cred_read, 20

globus_gsi_cred_read_cert, 21

globus_gsi_cred_read_cert_bio, 21

globus_gsi_cred_read_cert_buffer, 22

globus_gsi_cred_read_key, 21

globus_gsi_cred_read_pkcs12, 22

globus_gsi_cred_read_proxy, 20

globus_gsi_cred_read_proxy_bio, 20

globus_gsi_cred_write, 22

globus_gsi_cred_write_proxy, 23

GLOBUS_GSI_CRED_ERROR_BAD_PARAMETER

Credential Constants, 3	GLOBUS_GSI_CRED_ERROR_WITH_SSL_CTX
GLOBUS_GSI_CRED_ERROR_CHECKING_PROXY	Credential Constants, 3
Credential Constants, 2	GLOBUS_GSI_CRED_ERROR_WRITING_CRED
GLOBUS_GSI_CRED_ERROR_CREATING_ERROR-	Credential Constants, 2
OBJ	GLOBUS_GSI_CRED_ERROR_WRITING_PROXY_C-
Credential Constants, 3	RED
GLOBUS_GSI_CRED_ERROR_ERRNO	Credential Constants, 2
Credential Constants, 3	GLOBUS_GSI_CREDENTIAL_MODULE
GLOBUS_GSI_CRED_ERROR_GETTING_SERVICE-	Activation, 4
NAME	globus_gsi_cred_error_t
Credential Constants, 3	Credential Constants, 2
GLOBUS_GSI_CRED_ERROR_KEY_IS_PASS_PRO-	globus_gsi_cred_get_X509_identity_name
TECTED	Credential Handle Management, 11
Credential Constants, 3	globus_gsi_cred_get_X509_issuer_name
GLOBUS_GSI_CRED_ERROR_LAST	Credential Handle Management, 12
Credential Constants, 3	globus_gsi_cred_get_X509_subject_name
GLOBUS_GSI_CRED_ERROR_NO_CRED_FOUND	Credential Handle Management, 11
Credential Constants, 3	globus_gsi_cred_get_cert
GLOBUS_GSI_CRED_ERROR_READING_CRED	Credential Handle Management, 9
Credential Constants, 2	globus_gsi_cred_get_cert_chain
GLOBUS_GSI_CRED_ERROR_READING_HOST_C-	Credential Handle Management, 10
RED	globus_gsi_cred_get_cert_type
Credential Constants, 2	Credential Operations, 23
GLOBUS_GSI_CRED_ERROR_READING_PROXY_-	globus_gsi_cred_get_goodtill
CRED	Credential Handle Management, 8
Credential Constants, 2	globus_gsi_cred_get_handle_attrs
GLOBUS_GSI_CRED_ERROR_READING_SERVICE-	Credential Handle Management, 8
CRED	globus_gsi_cred_get_identity_name
Credential Constants, 2	Credential Handle Management, 13
GLOBUS_GSI_CRED_ERROR_SUBJECT_CMP	globus_gsi_cred_get_issuer_name
Credential Constants, 3	Credential Handle Management, 12
GLOBUS_GSI_CRED_ERROR_SUCCESS	globus_gsi_cred_get_key
Credential Constants, 2	Credential Handle Management, 10
GLOBUS_GSI_CRED_ERROR_SYSTEM_CONFIG	globus_gsi_cred_get_key_bits
Credential Constants, 3	Credential Handle Management, 9
GLOBUS_GSI_CRED_ERROR_VERIFYING_CRED	globus_gsi_cred_get_lifetime
Credential Constants, 2	Credential Handle Management, 8
GLOBUS_GSI_CRED_ERROR_WITH_CALLBACK_D-	globus_gsi_cred_get_policies
ATA	Credential Handle Management, 11
Credential Constants, 3	globus_gsi_cred_get_policy_languages
GLOBUS_GSI_CRED_ERROR_WITH_CRED	Credential Handle Management, 12
Credential Constants, 2	globus_gsi_cred_get_subject_name
GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT	Credential Handle Management, 11
Credential Constants, 2	globus_gsi_cred_handle_attrs_copy
GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT-	Credential Handle Attributes, 16
CHAIN	globus_gsi_cred_handle_attrs_destroy
Credential Constants, 3	Credential Handle Attributes, 16
GLOBUS_GSI_CRED_ERROR_WITH_CRED_CERT-	globus_gsi_cred_handle_attrs_get_ca_cert_dir
NAME	Credential Handle Attributes, 17
Credential Constants, 3	globus_gsi_cred_handle_attrs_get_search_order
GLOBUS_GSI_CRED_ERROR_WITH_CRED_HAND-	Credential Handle Attributes, 17
LE_ATTRS	globus_gsi_cred_handle_attrs_init
Credential Constants, 3	Credential Handle Attributes, 16
GLOBUS_GSI_CRED_ERROR_WITH_CRED_PRIV-	globus_gsi_cred_handle_attrs_set_ca_cert_dir
ATE_KEY	Credential Handle Attributes, 16
Credential Constants, 2	globus_gsi_cred_handle_attrs_set_search_order

- Credential Handle Attributes, 17
- globus_gsi_cred_handle_attrs_t
 - Credential Handle Attributes, 15
- globus_gsi_cred_handle_copy
 - Credential Handle Management, 7
- globus_gsi_cred_handle_destroy
 - Credential Handle Management, 7
- globus_gsi_cred_handle_init
 - Credential Handle Management, 7
- globus_gsi_cred_handle_t
 - Credential Handle Management, 7
- globus_gsi_cred_read
 - Credential Operations, 20
- globus_gsi_cred_read_cert
 - Credential Operations, 21
- globus_gsi_cred_read_cert_bio
 - Credential Operations, 21
- globus_gsi_cred_read_cert_buffer
 - Credential Operations, 22
- globus_gsi_cred_read_key
 - Credential Operations, 21
- globus_gsi_cred_read_pkcs12
 - Credential Operations, 22
- globus_gsi_cred_read_proxy
 - Credential Operations, 20
- globus_gsi_cred_read_proxy_bio
 - Credential Operations, 20
- globus_gsi_cred_set_cert
 - Credential Handle Management, 9
- globus_gsi_cred_set_cert_chain
 - Credential Handle Management, 10
- globus_gsi_cred_set_key
 - Credential Handle Management, 9
- globus_gsi_cred_type_t
 - Credential Constants, 3
- globus_gsi_cred_verify
 - Credential Handle Management, 14
- globus_gsi_cred_verify_cert_chain
 - Credential Handle Management, 13
- globus_gsi_cred_verify_cert_chain_when
 - Credential Handle Management, 13
- globus_gsi_cred_write
 - Credential Operations, 22
- globus_gsi_cred_write_proxy
 - Credential Operations, 23