

**globus rsl assist**  
2.2

Generated by Doxygen 1.7.3

Sat Apr 30 2011 06:52:17

# Contents

<b>1 RSL Helper Functions</b>	<b>1</b>
<b>2 Module Index</b>	<b>1</b>
2.1 Modules . . . . .	1
<b>3 Module Documentation</b>	<b>1</b>
3.1 RSL Helper Functions . . . . .	1
3.1.1 Detailed Description . . . . .	1
3.1.2 Function Documentation . . . . .	1

## 1 RSL Helper Functions

[RSL Helper Functions](#)

## 2 Module Index

### 2.1 Modules

Here is a list of all modules:

<a href="#">RSL Helper Functions</a>	1
--------------------------------------	---

## 3 Module Documentation

### 3.1 RSL Helper Functions

#### Functions

- int [globus\\_rsl\\_assist\\_attributes\\_canonicalize](#) ([globus\\_rsl\\_t](#) \**rsl*)
- void [globus\\_rsl\\_assist\\_string\\_canonicalize](#) (char \**ptr*)

#### 3.1.1 Detailed Description

The *rsl\_assist* library provide a set of functions to canonicalize RSL parse trees or strings.

#### 3.1.2 Function Documentation

##### 3.1.2.1 int [globus\\_rsl\\_assist\\_attributes\\_canonicalize](#) ( [globus\\_rsl\\_t](#) \* *rsl* )

Canonicalize all attribute names in an RSL parse tree.

The [globus\\_rsl\\_assist\\_attributes\\_canonicalize\(\)](#) function performs an in-place canonicalization of the RSL parse tree pointed to by its *rsl* parameter. All relation attribute names will be changed so that they lower-case, with all internal underscore characters removed.

#### Parameters

<i>rsl</i>	Pointer to the RSL parse tree to canonicalize.
------------	--

## Returns

If [globus\\_rsl\\_assist\\_attributes\\_canonicalize\(\)](#) is successful, it will ensure that all attribute names in the given RSL will be in canonical form and return GLOBUS\_SUCCESS. If an error occurs, it will return GLOBUS\_FAILURE.

## Return values

<i>GLOBUS_SUCCESS</i>	Success
<i>GLOBUS_FAILURE</i>	Failure

### 3.1.2.2 void [globus\\_rsl\\_assist\\_string\\_canonicalize\( char \\*ptr \)](#)

Canonicalize an attribute name.

The [globus\\_rsl\\_assist\\_string\\_canonicalize\(\)](#) function modifies the NULL-terminated string pointed to by its *ptr* parameter so that it is in canonical form. The canonical form is all lower-case with all underscore characters removed.

## Parameters

<i>ptr</i>	Pointer to the RSL string to modify in place.
------------	---

## Returns

void

## **Index**

globus\_rsl\_assist

    globus\_rsl\_assist\_attributes\_canonicalize, [1](#)

    globus\_rsl\_assist\_string\_canonicalize, [2](#)

globus\_rsl\_assist\_attributes\_canonicalize

    globus\_rsl\_assist, [1](#)

globus\_rsl\_assist\_string\_canonicalize

    globus\_rsl\_assist, [2](#)

RSL Helper Functions, [1](#)